

PRODUCT BENEFITS

- ▼ We dispense with a gearbox, which does not only reduce repair and maintenance costs. Even more important is a distinctly higher yield, especially in the partial-load range.
- ▼ The generator cooling system with air-to-air heat exchangers is fully encapsulated, protecting it from salty air, humidity, dust and dirt.
- ▼ High-quality permanent magnets prevent electrical excitation losses, additionally increasing the energy yield.
- ▼ The blade pitch system with a toothed belt drive is resistant to wear and requires little maintenance.

VENSYS 126

3.8 MW

VENSYS 126

3.8 MW

Operating data

Rated power	3.8 MW
Cut-in wind speed	3 m/s
Cut-out wind speed	25 m/s
Operating temperature	-20 °C to +40 °C

Sound power

Optimized for maximum performance	104.3 dB(A)
(Sound-reduced operating modes available)	

Rotor

Diameter	126.2 m
Swept area	12,509 m ²
Rotational direction	Clockwise
Rated speed	11.5 rpm
Blade type	EBT 61.6
Power control	Pitch
Primary braking system	Single-blade adjustment, triple redundant

Generator

Type	Synchronous generator with permanent magnet excitation
Construction type	Direct drive

Yaw system

Construction principle	Geared electric motors
Braking system	Hydraulic brake calipers

Converter

Type	IGBT full power converter
Frequency	50 Hz / 60 Hz

Tower

Hub heights	
86.9 m 96.9 m	Steel tube tower
116.9 m	Segmented steel tower
136.9 m	Hybrid tower (concrete/steel)

Wind class

Hub heights 86.9 m 96.9 m	IEC IIA
Hub height 116.9 m	IECS
Hub height 136.9 m	IEC IIIA



POWER CURVE VENSYS 126

Ø Wind speed [m/s]	AEP [MWh]
5.0	6,508.7
5.5	8,120.8
6.0	9,750.4
6.5	11,350.5
7.0	12,887.6
7.5	14,339.0
8.0	15,689.9
8.5	16,930.6

