

TECHNICAL DATA



PRODUCT BENEFITS

- ▼ The ongoing reduction of energy costs will be continued with this platform
- ▼ Transport optimisation through segmented design of components
- ▼ Thirty years of experience using permanent magnet technology

VENSYS **155**

6.2 MW

VENSYS 155

6.2 MW



Operating data

Rated power	6.2 MW
Cut-in wind speed	3 m/s
Cut-out wind speed	25 m/s
Operating temperature	-20 °C to +40 °C
(De-rating possible from 30 °C)	

Sound power level

Optimized for maximum performance <105.0 dB(A)
(Sound-optimised operating modes available)

Rotor

Diameter	155.0 m
Swept area	18,869 m ²
Rotational direction	Clockwise
Blade type	EBT 76
Power control	Pitch
Primary braking system	Single-blade adjustment, triple redundant

Generator

Type	Synchronous generator with permanent magnet excitation
Construction type	Direct drive

Yaw system

Construction principle	Geared electric motors
Braking system	Hydraulic brake calipers

Converter

Type	IGBT full power converter
Frequency	50 Hz / 60 Hz

Tower

Hub heights	102.5 m 122.5 m	Segmented steel tower
152.5 m		Hybrid tower (concrete / steel)

Design

Hub heights 102.5 m 122.5 m	IEC IIA
Hub height 152.5 m	IEC IIIA

POWER CURVE VENSYS 155

Wind speed [m/s]	AEP [MWh]
5,0	9,724.4
5,5	12,246.6
6,0	14,828.3
6,5	17,391.0
7,0	19,875.5
7,5	22,240.2
8,0	24,456.2
8,5	26,503.7

