

 TECHNICAL DATA

- ▼ The ongoing reduction of energy costs will be continued with this platform
- ▼ Even more efficient transport optimisation through segmented design of components
- ▼ Thirty years of experience using permanent magnet technology

VENSYS 175

7.8 MW

VENSYS 175

7.8 MW



Operating data

Rated power	7.8 MW
Cut-in wind speed	3 m/s
Cut-out wind speed	24 m/s
Operating temperature	-20 °C to +40 °C
(De-rating possible from 30 °C)	

Sound power level

Performance-optimized	106.5 dB(A)
(Sound-optimized operating modes available)	

Rotor

Diameter	175 m
Swept area	24,053 m ²
Rotational direction	Clockwise
Rated speed	9 rpm
Blade type	GW 86
Power control	Pitch
Primary braking system	Aerodynamic by feathering blades (triple redundant)

Generator

Type	Medium-speed synchronous generator with permanent magnet excitation
------	---

Gear box

Type	3-stage planetary gearbox
------	---------------------------

Yaw system

Actuation	Geared electric motors
Bearing	Sliding bearing

Converter

Type	IGBT full power converter
Frequency	50 Hz / 60 Hz

Tower

Hub heights	
145 m	Segmented steel tower
160 m	Hybrid tower (concrete / steel)

Wind class

All hub heights	IEC S
-----------------	-------

POWER CURVE VENSYS 175

Ø Wind speed [m/s]	AEP [MWh]
5,0	12,449.0
5,5	15,743.5
6,0	19,102.2
6,5	22,416.8
7,0	25,604.7
7,5	28,605.3
8,0	31,375.7
8,5	33,885.7

Power (kW)

