

PRODUCT BENEFITS

- ▼ Dispensing with a gearbox means lower repair and maintenance costs and a higher yield.
- ▼ High-quality permanent magnets prevent electrical excitation losses, which additionally increases the energy yield.
- ▼ The air-cooling system used for the generator and the VENSYS frequency converter saves on additional components, cooling agents and maintenance work.
- ▼ The blade pitch system with a toothed belt drive is lubrication-free, resistant to wear and requires little maintenance.

A detailed 3D rendering of a wind turbine nacelle, showing the internal components like the generator and frequency converter, and the three blades extending from the hub. The nacelle is white with blue accents.

VENSYS 82

1.85 MW

VENSYS 82

1.85 MW



Operating data

Rated power	1.85 MW
Cut-in wind speed	3 m/s
Cut-out wind speed	25 m/s
Operating temperature	-20 °C to +40 °C
(De-rating possible from 30 °C)	

Sound power

Optimized for maximum performance	105.8 dB(A)
(Sound-reduced operating modes available)	

Rotor

Diameter	82.3 m
Swept area	5,320 m ²
Rotational direction	Clockwise
Rated speed	18.25 rpm
Blade type	EBT 40
Power control	Pitch
Primary braking system	Single-blade adjustment, triple redundant

Generator

Type	Synchronous generator with permanent magnet excitation
Construction type	Direct drive

Yaw system

Construction principle	Geared electric motors
Braking system	Hydraulic brake calipers

Converter

Type	IGBT full power converter
Frequency	50 Hz / 60 Hz

Tower

Hub heights 58.7 m 83.7 m 100 m	Steel tube tower
-------------------------------------	------------------

Wind class

Hub heights 58.7 m 83.7 m 100 m	IEC IIA
-------------------------------------	---------

POWER CURVE VENSYS 82

Wind speed [m/s]	AEP [MWh]
5.0	2,904.3
5.5	3,666.0
6.0	4,446.8
6.5	5,221.8
7.0	5,972.6
7.5	6,686.3
8.0	7,354.0
8.5	7,969.9

