

PRODUCT BENEFITS

- ▼ Dispensing with a gearbox means lower repair and maintenance costs and a higher yield.
- ▼ High-quality permanent magnets prevent electrical excitation losses, which additionally increases the energy yield.
- ▼ The air-cooling system used for the generator and the VENSYS frequency converter saves on additional components, cooling agents and maintenance work.
- ▼ The blade pitch system with a toothed belt drive is lubrication-free, resistant to wear and requires little maintenance.

The text "VENSYS 82" in a large, blue, sans-serif font. The "82" is significantly larger than "VENSYS". The background is a detailed 3D rendering of a wind turbine nacelle and hub, showing the internal structure and the three blades extending from the hub. The nacelle is white with a blue triangle logo on the side. The hub is a large, spherical component with a blue triangle logo. The blades are white with a blue triangle logo on the leading edge. The background features a light blue, wavy, abstract pattern.

1.85 MW

VENSYS 82

1.85 MW



Operating data

Rated power	1.85 MW
Cut-in wind speed	3 m/s
Cut-out wind speed	25 m/s
Operating temperature	-20 °C to +40 °C
(De-rating possible from 30 °C)	

Sound power

Optimized for maximum performance	105.8 dB(A)
(Sound-reduced operating modes available)	

Rotor

Diameter	82 m
Swept area	5,281 m ²
Rotational direction	Clockwise
Rated speed	18.25 rpm
Blade type	EBT 40
Power control	Pitch
Primary braking system	Single-blade adjustment, triple redundant

Generator

Type	Synchronous generator with permanent magnet excitation
Construction type	Direct drive

Yaw system

Construction principle	Geared electric motors
Braking system	Hydraulic brake calipers

Converter

Type	IGBT full power converter
Frequency	50 Hz / 60 Hz

Tower

Hub heights	58.7 m 83.7 m 100 m
Material	Steel tube tower

Wind class

All hub heights	IEC IIA
-----------------	---------

POWER CURVE VENSYS 82

Ø Wind speed [m/s]	AEP [MWh]
5.0	2,904.3
5.5	3,666.0
6.0	4,446.8
6.5	5,221.8
7.0	5,972.6
7.5	6,686.3
8.0	7,354.0
8.5	7,969.9

