

TECHNICAL DATA

PRODUCT BENEFITS

- ▼ Dispensing with a gearbox means lower repair and maintenance costs and a higher yield.
- ▼ High-quality permanent magnets prevent electrical excitation losses, which additionally increases the energy yield.
- ▼ The generator cooling system with air-to-air heat exchangers is fully encapsulated, protecting it from salty air, humidity, dust and dirt.
- ▼ The blade pitch system with a toothed belt drive is lubrication-free, resistant to wear and requires little maintenance.

VENSYS *100*

2.5 MW

VENSYS 100

2.5 MW



Operating data

Rated power	2.5 MW
Cut-in wind speed	3 m/s
Cut-out wind speed	25 m/s
Operating temperature	-20°C bis +40°C

Sound power

Optimized for maximum performance	105.1 dB(A)
(Sound-reduced operating modes available)	

Rotor

Diameter	99.8 m
Swept area	7,823 m ²
Rotational direction	Clockwise
Rated speed	14.5 rpm
Blade type	LM 48.8
Power control	Pitch
Primary braking system	Single-blade adjustment, triple redundant
Holding brake	Hydraulic with locking bolt

Generator

Type	Synchronous generator with permanent magnet excitation
Construction type	Direct drive

Yaw system

Construction principle	Geared electric motors
Braking system	Hydraulic brake calipers

Converter

Type	IGBT full power converter
Frequency	50 Hz / 60 Hz

Tower

Hub heights	75 m 100 m
Material	Steel tube

Design

Hub height 75 m	DIBtWZ 3; IEC IIA
Hub height 100 m	DIBtWZ 2; IEC IIIA

POWER CURVE VENSYS 100

Wind speed m/s	AEP [MWh] VENSYS 100 - LM 48.8
5.0	3,870.5
5.5	4,897.2
6.0	5,950.8
6.5	6,997.7
7.0	8,012.9
7.5	8,978.5
8.0	9,882.7
8.5	10,717.3

Power (kW)

